

## Eaton E Series DX



**Technology:** Series 9 (Double Conversion On Line)  
**Rating:** 1kVA – 20kVA  
**Voltage:** 230/240V  
**Backup Time:** Typical 5 min  
**Configuration:** Tower

The E Series<sup>®</sup> DX UPS double-conversion UPS affordably protects mission critical applications from downtime, data loss and corruption. The double-conversion architecture incorporates rectifier and inverter stages to completely isolate the output power from all input anomalies. By adapting to a wide range of input voltages, the E Series DX avoids battery usage during minor power fluctuations, saving its capacity for times when utility power is completely lost.

### Ideal for protecting

- Computers and Peripherals
- POS Equipment
- PLC Systems
- Security Systems

### Features

- Double conversion topology assures maximum reliability
- Wide input voltage range appropriate for the harshest electrical environments
- Tested for generator compatibility
- Standard Models for fixed-run time performance
- XL Models for customised, long run-time applications, with fast recharging
- Automatic bypass for fault-tolerance
- Built in maintenance bypass on 6-20kVA models
- Optional SNMP communications provides remote network based monitoring
- Cold start on battery power allows portable power
- WINPOWER software monitors power conditions
- Intuitive front-panel LED user interface for consistent status indication
- 6-20kVA models are parallelable for increased capacity and/or redundancy

### Options

- SNMP/Web Card
- Relay Card
- Modbus Card
- External Maintenance Bypass Switch
- Extended Battery Cabinets



3kVA rear panel